

使用用途・機器	形式	定格容量 (mAh)	公称電圧 (V)	寸法(チューブ付)		質量 (約g)	標準電圧		JIS形式
				D	H		電流(mA)	時間(hr)	
一般用	AA90	90	1.2	14.5	17.5	7	9	16	KR15/18
	AA100	100		14.5	17.5	7	10	16	KR15/18
	AA225	225		14.5	30.0	13	22.5	16	KR15/30
	AA250	250		14.5	30.0	13	25	16	KR15/30
	AA450	450		14.5	49.0	23	45	16	KR15/49
	AA500	500		14.5	49.0	23	50	16	KR15/49
	AA600	600		14.5	49.0	23	60	16	KR15/49
	SC1.2	1200		23.0	43.0	51	120	16	KR23/43
	C1.7	1650		25.8	50.0	85	165	16	KR26/50
	C1.8	1800		25.8	50.0	85	180	16	KR26/50
	C2.0	2000		25.8	50.0	85	200	16	KR26/50
	D3.5	3500		33.0	60.0	165	350	16	-
	D4.0	4000		33.0	60.0	165	400	16	-
	F6.0	6000		33.0	91.0	220	600	16	KR33/91
	M8.0	8000		43.5	71.0	285	800	16	-
M10.0	10000	43.5	91.0	365	1000	16	KR44/91		
高温トリクル用	SC1.2H	1200	1.2	23.0	43.0	47	40	48~	KR23/43
	C1.7H	1650		25.8	50.0	75	55	48~	KR26/50
	C1.8H	1800		25.8	50.0	75	60	48~	KR26/50
	C2.0H	2000		25.8	50.0	75	67	48~	KR26/50
	C2.3H	2300		25.8	50.0	77	77	48~	KR26/50
	C2.5H	2500		25.8	50.0	77	83	48~	KR26/50
	D3.5H	3500		33.0	60.0	155	117	48~	-
	D4.0H	4000		33.0	60.0	155	133	48~	-